

Stainless Steel DEEPBUBBLE™ Multi-Stage Aeration



*MODEL DB-64
shown*

- HIGH CAPACITY
- HIGH-EFFICIENCY
DEEP STAGES
- LOW MAINTENANCE
- INSULATED
NO-SWEAT TANK

SPECIFICATIONS:	DB88	DB86	DB84	DB63	DB62	DB32
Number of Stages	8	8	8	6	6	3
Max Flow, gpm	2000	1000	600	300	150	50
Max Air, cfm		varies with aerator type and application				
Dimensions:						
Length	20'-5"	12'-5"	12'-3"	8'-3"	8'-3"	4'-3"
Width	8'-5"	6'-5"	4'-3"	3'-3"	2'-3"	2'-3"
Height	6'-6"	6'-6"	5'-5"	4'-5"	4'-5"	3'-5"
Inlets/Outlets	standard Sch 80 flanges or couplers - sizes varies with design flow rate					
Vessel Material	304 SS or 316 SS (optional)					
Aerators	Type I PVC in several interchangeable orifice sizes					
Operating Weight, lbs	36,000	21,000	11,000	6,000	4,500	1,400
Empty (shipping) Weight, lbs	6,000	3,000	2,000	2,000	1,500	550

NOTE: specifications subject to change without notice

DEEPBUBBLE Multi-Stage Aeration Systems are furnished complete with blower(s), filter silencer(s), and accessories with Lowry Aeration Systems' guarantee of performance. Optional accessory equipment including control panels, repumping and storage options are also available.

LOWRY
AERATION SYSTEMS

146 South Street
Blue Hill, ME 04614

*Designs & Quotations
CALL 800 - 434 - 9080*